



# FIRE FIGHTING TRAILER – FIRE SCOUT PUMP SPECIFICATION SHEET



SRFQ1000LZ

**1000 LITRE**  
**SINGLE AXLE TRAILER**

## TRAILER SPECIFICATIONS

TYPE	FARM	Standard trailer - no lights, reflectors or brakes
	ROAD	Fitted with LED lights, reflectors, brakes & compliance plate - to ADR standards
CHASSIS		Fully welded RHS steel - galvanised steel construction, galvanised mudguards
RUNNING GEAR	AXLES	Single, 45mm square, mounted over 6 leaf springs
	WHEELS	14" x 6" – 5 Stud Ford pattern
	TYRES	Brand new, All Terrain Light Truck tyres 185R 14C
BRAKES	HYDRAULIC	Hydraulic override operation 9" drum brakes with master cylinder
TOWING		50mm Ball Hitch, 7 pin flat trailer plug, safety chains
AGGREGATE TRAILER MASS (AGM)		1500 kg
DIMENSIONS		3480mm (L) x 1770mm (W) x 1375mm (H)

## FIRE KITS

- Poly reel with galvanised steel mounting frame fitted with 36metres x 19mm fire hose (AS1221) & adjustable fire fighting nozzle.
- Full flow brass swivel fitted to reel
- Bottom fill kit – 6 metres of hose and suction filter
- Camlock fittings used standard – 1 1/2"



## MOTOR SPECIFICATIONS

ENGINE SPECS	DESCRIPTION	MAX. POWER	CONTINUOUS POWER	DRY WEIGHT	FUEL TANK CAPACITY	OIL TYPE	OIL CAPACITY	ELECTRIC START
Honda GX160	Single cylinder petrol with oil alert	4.8hp @ 3600rpm	3.9hp @ 3600rpm	15 kg	3.6 litres	10W/30	0.6 litres	No
Yanmar L48N	Single cylinder diesel	4.7hp @ 3600rpm	4.2hp @ 3600rpm	27 kg	2.4 litres	30W	0.8 litres	Optional

## PUMP KITS – STANDARD FIRE KIT

PUMP MODEL	MAX. HEAD	MAX. FLOW	POWERED BY	WEIGHT	DIMENSIONS
APF3500Z	72m	390LPM	Honda GX160	24.2kg	380(H)x385(W)x480(L)

## PUMP CONSTRUCTION/STANDARD FEATURES

- 1 x 1 1/2" suction port
- 1 x 1 1/2" discharge port
- 2 x 1" discharge port
- Oil sensor
- 3-way outlet
- Suction head 8m
- Max head 72m
- Max flow volume 390L/min
- Heavy duty powder coated skid with anti-vibration mounts

APF3500Z FLOW CURVE

